

TOPLA TOP utilises the latest innovations in Ca/Ca manufacturing technology, providing for the highest cold start performance and superior reliable power as demanded by the latest generation of cars with high energy drain. The SMF lid/cover provides complete roll over spill protection and is entirely maintenance free throughout the batteries life.

- + Sealed cover construction
- + Higher number of plates ensure 30% better starting capabilities
- + The expanded metal technology results in better corrosion resistance and providing a longer life time
- + The level indicator (magic eye) provides an instant status check
- + Explosion protection prevents flame brake-into the battery
- + Ideal for cars with lots of electrical equipment
- + Battery of highest quality



TOPLA TOP

Flooded starter batteries, Ca/Ca technology | CAR batteries

Art. №	DIN marking	Short code	C20 (Ah)	Box Type	EN (A)	LxWxH (mm)	BHD	Layout	Weight (kg)	PCS per Pallet (EUR/CNT)	Remarks
118654	55401 SMF	TT54	54	L1B	510	207x175x175	B13	0	12,3	60/120	SMF, ME, H
118655	55510 SMF	TT55H	55	L1	550	207x175x190	B13	0	13,4	60/100	SMF, ME, H
118662	56249 SMF	TT62	62	L2B	600	242x175x175	B13	0	14,6	57/108	SMF, ME, H
118666	56649 SMF	TT66H	66	L2	640	242x175x190	B13	0	15,0	57/90	SMF, ME, H
118072	57510 SMF	TT75	75	L3B	720	278x175x175	B13	0	17,1	48/80	SMF, ME, H, HD
118678	57549 SMF	TT78H	78	L3	780	278x175x190	B13	0	17,8	48/80	SMF, ME, H, HD
118685	58514 SMF	TT85	85	L4B	800	315x175x175	B13	0	19,0	36/72	SMF, ME, H, HD
118600	60032 SMF	TT100	100	L5B	950	353x175x175	B13	0	22,2	36/72	SMF, ME, H, HD

TOPLA TOP JIS

Flooded starter batteries, Ca/Ca technology | CAR batteries

Art. №	DIN marking	JIS marking (OLD/NEW)	Short code	C20 (Ah)	Box Type	EN (A)	LxWxH (mm)	BHD	Layout	Weight (kg)	PCS/Pallet (EUR/CNT)	Remarks
118835	53520 SMF	NS40ZL SMF/36B20L SMF	TT35J	35	53520	300	196x127x205/226	B0	0	9,5	96/128	SMF, H, JIS
118935	53522 SMF	NS40Z SMF/36B20R SMF	TT35X	35	53522	300	196x127x205/226	B0	1	9,5	96/128	SMF, H, JIS
118735	53520 SMF	NS40ZL SMF/36B20L SMF	TT35P	35	53520	300	196x134x205/226	B01	0	9,5	96/128	SMF, H, JIS
118245	54520 SMF	NS60LS BHD	TT45J	45	53520	400	196x134x205/226	B1	0	10,5	72/96	/
118145	54522 SMF	NS60S BHD	TT45X	45	53522	400	196x134x205/226	B1	1	10,5	72/96	/
118845	54523/84 SMF	NS60LS SMF/46B24LS SMF	TT45JA	45	54523/84	400	237x127x205/226	B0	0	11,9	72/96	SMF, H, JIS, A
118945	54524/51 SMF	NS60S SMF/46B24RS SMF	TT45AX	45	54524/51	400	237x127x205/226	B0	1	11,9	72/96	SMF, H, JIS, A
118255	55523/84 SMF		TT55J	55	54523/84	540	237x127x205/226	B0	0	13,7	72/96	SMF, H, JIS, A
118355	55524/51 SMF		TT55X	55	54524/51	540	237x127x205/226	B0	1	13,7	72/96	SMF, H, JIS, A
118860	56068 SMF	NS0ZL SMF/55D23L SMF	TT60J	60	56068	600	230x172x200/220	B01	0	14,9	60/90	SMF, H
118960	56069 SMF	NS0Z SMF/55D23R SMF	TT60X	60	56069	600	230x172x200/220	B01	1	14,9	60/90	SMF, H
118665	56568 SMF		TT65J	65	56068	650	230x172x200/220	B01	0	15,4	60/90	SMF, H
118765	56569 SMF		TT65X	65	56069	650	230x172x200/220	B01	1	15,4	60/90	SMF, H
118870	57029 SMF	NS70L SMF/65D26L SMF	TT70J	70	57029	700	269x173x198/218	B9	0	16,8	48/80	SMF, H
118970	57024 SMF	NS70 SMF/65D26R SMF	TT70X	70	57024	700	269x173x198/218	B9	1	16,8	48/80	SMF, H
118875	57529 SMF		TT75J	75	57029	740	269x173x198/218	B9	0	17,1	48/80	SMF, H
118975	57524 SMF		TT75X	75	57024	740	269x173x198/218	B9	1	17,1	48/80	SMF, H
118895	59518 SMF	Nx120-7L SMF/105D31L SMF	TT95J	95	59518	850	303x174x198/218	B01	0	20,6	42/70	SMF, H
118995	59519 SMF	Nx120-7 SMF/105D31R SMF	TT95X	95	59519	850	303x174x198/218	B01	1	20,6	42/70	SMF, H

TOPLA TOP SEALED TRUCK

Flooded starter batteries, Ca/Ca technology | TRUCK batteries

Art. №	DIN marking	Short code	C20 (Ah)	Box Type	EN (A)	LxWxH (mm)	BHD	Layout	Weight (kg)	PCS per Pallet (EUR/CNT)	Remarks
243612	63544 SMF	TT13M	135	MAC110	850	509x175x182/208	B3	3	34,9	24/40	SMF, ME, H, HD
231612	64030 SMF	TT14	140	A	850	513x189x194/220	B0	3	36,8	24/35	SMF, ME, H, HD
216612	65048 SMF	TT15M	150	MAC110	1000	509x175x182/208	B3	3	36,9	24/40	SMF, ME, H, HD
244612	65018 SMF	TT15	150	B	950	512x222x202/229	B0	3	40,4	24/32	SMF, ME, H, HD
245612	67018 SMF	TT17	170	B	1050	512x222x202/229	B0	3	43,7	21/28	SMF, ME, H, HD
258612	67018 SMF	TT18	180	B	1050	512x222x202/229	B0	3	43,7	21/28	SMF, ME, H, HD
223612	70027 SMF	TT20	200	C	1200	513x275x220/247	B0	3	53,8	18/24	SMF, ME, H, HD
125612	72527 SMF	TT22	225	C	1300	513x275x220/247	B0	3	57,2	18/24	SMF, ME, H, HD